



















## RUBBER CABLES

DENOMINATION	CODE	RATED VOLTAGE U <sub>0</sub> /U	Ø CROSS SECTION	DIMENSIONS +/- 0,2mm	PROFILE
Ordinary rubber sheathed flexible cord	H05RR-F	300 / 500V	2X0.75	6.2	
			2X1	6.8	
			2X1.5	8.3	
			2X2.5	9.7	
			3G0.75	6.7	
			3G1	7.2	
			3G1.5	8.8	
			3G2.5	10.2	
Ordinary polychloroprene sheathed flexible cord	H05RN-F	300 / 500V	2X0.75	6.2	
			2X1	6.8	
			3G0.75	6.7	
			3G1	7.2	
Tough polychloroprene sheathed flexible cord for water immersion	H07RN-F	450 / 750V	2X1	8.1	
			2X1.5	9.3	
			2X2.5	10.8	
			3G1	9	
			3G1.5	10	
			3G2.5	11.7	
			4 G1	10	
			4G1.5	11	
			4G2.5	13	
			5G1	10.9	
			5G1.5	12	
			5G2.5	14	










## RUBBER CABLES

DENOMINATION	CODE	RATED VOLTAGE U <sub>0</sub> /U	Ø CROSS SECTION	DIMENSIONS +/- 0,2mm	PROFILE
Tough polychloroprene sheathed flexible cord for water immersion	H07RN8-F	450 / 750V	2X1	8.1	
			2X1.5	9.3	
			2X2.5	10.8	
			3G1	9	
			3G1.5	10	
			3G2.5	11.7	
			4G1	10	
			4G1.5	11	
			4G2.5	13	
			5G1	10.9	
			5G1.5	12	
			5G2.5	14	
			Tough polychloroprene sheathed flexible cord oil resistant	H07BN4-F (T.Max 90°C)	450 / 750V
2X1.5	9.3				
2X2.5	10.8				
3G1	9				
3G1.5	10				
3G2.5	11.7				
Light rubber sheathed flexible cord	SV	300 V	2X18 AWG	6.3	
			2X16 AWG	6.7	
			3X18 AWG	6.6	
			3X16 AWG	6.9	

## RUBBER CABLES

DENOMINATION	CODE	RATED VOLTAGE U <sub>0</sub> /U	Ø CROSS SECTION	DIMENSIONS +/- 0,2mm	PROFILE
Light rubber sheathed flexible cord oil resisting	SVO	300V	2X18 AWG	6.3	
			2X16 AWG	6.7	
			3X18 AWG	6.6	
			3X16 AWG	6.9	
Ordinary rubber sheathed flexible cord	SJ	300V	2X18 AWG	7.6	
			2X16 AWG	8.2	
			2X14 AWG	8.9	
Ordinary rubber sheathed flexible cord water resisting	SJW		3X18 AWG	8.3	
			3X16 AWG	8.9	
			3X14 AWG	9.4	
Ordinary rubber sheathed flexible cord oil resisting	SJO	300 V	2X18 AWG	7.6	
			2X16 AWG	8.2	
			2X14 AWG	8.9	
Ordinary rubber sheathed flexible cord oil and water resisting	SJOW		3X18 AWG	8.3	
			3X16 AWG	8.9	
			3X14 AWG	9.4	

## OTHER CABLES INCLUDED IN OUR RANGE

DENOMINATION	TYPE	U <sub>o</sub> /U	CROSS SECTION	DIMENSIONS +/- 0,2mm	PROFILE	
Rubber (T. Max 90°C) Multicore sheathed cable, heat resistant	H05BB-F	300 / 500V	2X0.75	6.2		
			2X1	6.8		
			2X1.5	8.3		
			2X2.5	9.7		
			3G0.75	6.7		
				3G1		7.2
				3G1.5		8.8
				3G2.5		7.6
Rubber (T. Max 90°C) Multicore sheathed cable, heat resistant	H07BB-F	450 / 750V	2X1	8.1		
			2X1.5	9.3		
			2X2.5	10.8		
			3G1	9		
			3G1.5	10		
			3G2.5	11.7		
Rubber (T. Max 110°C) Multicore sheathed cable, heat resistant	H05GG-F	300 / 500V	2X0,75	6.2		
			2X1	6.6		
			2X1.5	7.6		
			2X2.5	9.2		
			3G0.75	6.6		
			3G1	7.0		
			3G1.5	8.3		
			3G2.5	10.0		
			4G0,75	6.8		
			4G1	8.0		
			4G1.5	9.4		
			4G 2.5	11		
			5G0.75	7.2		
			5G1	8.8		
			5G1.5	10.5		
5G2.5	12.3					

## SYSTEM FOR DESIGNATION OF HARMONIZED CABLES

<div style="border: 1px solid black; width: 30px; height: 30px; display: flex; align-items: center; justify-content: center; margin: 0 auto;">1</div>	<p style="text-align: center;">H A</p>	<p><b>SPECIFICATION REFERENCE</b>            Cable according to harmonized specification.            Recognized national type of cable.</p>
<div style="border: 1px solid black; width: 30px; height: 30px; display: flex; align-items: center; justify-content: center; margin: 0 auto;">2</div>	<p style="text-align: center;">3 5 7</p>	<p><b>RATED VOLTAGE U<sub>0</sub>/U</b>            U<sub>0</sub>/U = 300/300 V            U<sub>0</sub>/U = 300/500 V            U<sub>0</sub>/U = 450/750 V</p>
<div style="border: 1px solid black; width: 30px; height: 30px; display: flex; align-items: center; justify-content: center; margin: 0 auto;">3</div>	<p style="text-align: center;">V R</p>	<p><b>INSULATING MATERIALS</b>            Polyvinyl-chloride.            Synthetic rubber.</p>
<div style="border: 1px solid black; width: 30px; height: 30px; display: flex; align-items: center; justify-content: center; margin: 0 auto;">4</div>	<p style="text-align: center;">V R N T</p>	<p><b>SHEATH MATERIALS</b>            Polyvinyl-chloride.            Synthetic rubber.            Polychloroprene.            Textile braid.</p>
<div style="border: 1px solid black; width: 30px; height: 30px; display: flex; align-items: center; justify-content: center; margin: 0 auto;">5</div>	<p style="text-align: center;">H H2</p>	<p><b>SPECIAL CONSTRUCTIONS AND SHAPES</b>            Flat construction of divisible cables.            Flat construction of non-divisible cables.</p>
<div style="border: 1px solid black; width: 30px; height: 30px; display: flex; align-items: center; justify-content: center; margin: 0 auto;">6</div>	<p style="text-align: center;">F H</p>	<p><b>TYPE OF CONDUCTOR</b>            Flexible conductor.            High flexible conductor.</p>
<div style="display: flex; gap: 10px;"> <div style="border: 1px solid black; width: 30px; height: 30px; display: flex; align-items: center; justify-content: center; margin: 0 auto;">7</div> <div style="border: 1px solid black; width: 30px; height: 30px; display: flex; align-items: center; justify-content: center; margin: 0 auto;">8</div> </div>	<p style="text-align: center;">G X</p>	<p><b>NUMBER OF CORES</b>            With green/yellow wire.            Without green/yellow wire.</p>
<div style="border: 1px solid black; width: 30px; height: 30px; display: flex; align-items: center; justify-content: center; margin: 0 auto;">9</div>		<p><b>NOMINAL CROSS SECTION CONDUCTOR (mm<sup>2</sup>)</b></p>